



COBRA HDT-V COMPACT

HD-TVI COMPACT 4 CHANNEL DVR

The Cobra HDT-V Compact 4 channel recorder now has real-time 25FPS recording across all channels at a cost effective full HD 1080P price point. The Cobra C-HDT-V model will now accept HD-TVI, HD-CVI & Analogue cameras at full HD 1080P. Despite its small form, it packs an incredible punch and we would challenge anyone to find a better performing full HD TVI or AHD recorder at this price point!

C-HDT-V 4

KEY FEATURES

- 4ch HD (1080P) Real-time recording
- 4ch 960H Analogue Real-time Recording
- Full HD 1080p Video Out Display (HDMI)
- Hybrid DVR compatible with HD-TVI, Analogue, AHD and HD-CVI
- 1 Audio Input - Auto port forwarding - Free DDNS
- Up to 6TB of HDD storage
- User-friendly GUI & Design
- Smart & Event Search – save time looking through footage!
- Motion Detection - Offers up the coax control
- Various Network Software – VMS, RMS, Web Viewer, Mac Viewer
- Fast Smartphone access full features live & playback
- Supplied with mouse and IR remote

SPECIFICATION

Model	C-HDT-V 4
System	
Time Accuracy	2ppm (5sec/month)
Time Sync.	NTP, GMT, DST, Time Server
User	15 Users (admin, user1 ~ user14)
Video	
Input	4 BNC
Output	1BNC,1VGA,1HDMI
Loop	N/A
Spot	N/A
Audio	
Input	1 RCA + 3RCA (EXT.)
Output	1 RCA
Video Recording	
Resolution	Max. D1, 2CIF, CIF
Quality	5 Levels
Audio Recording	
Compression	G.723
Network	
Interface	Ethernet 10/100
Compression	H.264
Speed	CIF real-time
Resolution	CIF, 2CIF, 4CIF
Alarm	
Pre/Post-Alarm	5sec / 5sec~5min
Motion Grid	22x15(NTSC) / 22x18(PAL)
Input / Output	4/1 - NC/NO
Display	
HDMI	1080P
VGA	XGA(1024x768)
TV	SDTV(720x480/576)
External Interface	
PTZ	RS485 - Terminal Block
ATM/POS	N/A
Storage	
Primary	1 HDD
General	
OS	Embedded Linux
Dimension	250x65x155mm
Net Weight(w/o HDD)	2.5Kg
Power Supply	12V/2A - Level 5
Compsumption	24Watts
Operating Temp	5 ~ 40 C
Humidity	10 ~ 80%



•HD-TVI Compact
4 channel DVR
back of the DVR