





COBRA₅

4 , 8 , & 16 c h D V R



COBRA_S

SPECIFICATION

Model Name		COBRA _S 16ch	COBRA _S 8ch	COBRA _S 4ch
	Front			
Case	Rear			
Video	Input	16 BNC + 4 IP	8 BNC + 2 IP	4 BNC + 1 IP
	Input Resolution	5MP, 4MP, 3MP, 2MP, 960H		
	Output	1 HDMI, 1 VGA, 1 BNC		
	Output Resolution	4K, FHD, SXGA		
Recording	Speed	10fps/ch (5MP), 15fps/ch (4MP), 30fps/ch (2MP)		
	Compression	H.265, H.264		
	Resolution	5MP, 4MP, 3MP, 2MP, 960H		
Audio	Input	4 RCA + 12 D-SUB	8 RCA	4 RCA
	Output	1 HDMI, 1 RCA		
Interface	Sensor In / Out	16 / 1 - NC / NO	8 / 1 - NC / NO	4 / 1 - NC / NO
	USB	2 x USB 2.0		
	PTZ / Keyboard	RS485 - Terminal Block		
	ATM / POS	Ethernet POS		
Network	Interface	Ethernet 10/100/1G		
	Compression	H.264, JPEG		
	Speed	10fps (4MP), 20fps (2MP)		
	Resolution	Max. 4MP		
System	OS	Embedded Linux (Built-in Flash Memory)		
	Pre / Post-Alarm	5sec / 5sec-5min		
	Recording Mode	Continuous, Event, Schedule		
	Data Search	Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time		
	Backup Interface	USB, Network		
	Backup Type	Video (RMS, AVI), Capture (JPEG), Log List, Setup Data		
	Alarm Action	Buzzer, PTZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push		
	User	15 Users (Admin, User1 - User14)		
	Network Viewer	Netus, VMS, Web Viewer, Mac Viewer, SmartEyesPro (iOS, Android)		
	ONVIF	ONVIF Profile S		
Storage	Primary	2 HDD		1 HDD
General	Size (W x H x D)	378 x 50 x 340 mm		300 x 53 x 227 mm
	Weight (w/o HDD)	3 Kg		2 Kg
	Temp / Humidity	5 - 40°C / 10 - 80%		
	Power Supply	12V / 5A		12V / 2A
	Power Consumption	60 Watts		24 Watts