




# 5MP HD ColorHunter Fixed Eyeball Network Camera

UIPC3615SE-ADF28KM-WL-I0




30M IR  
SMART IR

## KEY FEATURES

- High quality image with 5MP, 1/2.7" F1.0 CMOS sensor
- 5MP (2880\*1620)@25fps; 4MP (2560\*1440)@25fps;3MP (2304\*1296)@25fps; 2MP (1920\*1080)@ 30/25fps;;
- Ultra 265, H.265, H.264, MJPEG
- Colorhunter technology ensures 24-hour full-color images
- 120dB true WDR technology enables clear image in strong light scene
- 9:16 corridor Mode
- Built-in Mic
- Up to 256 G Micro SD card
- IP67 protection
- 30M white light LED

## DIMENSIONS



## BRACKETS



Pole Mount Bracket  
Code: UTR-UP06-C-IN  
(Needs: UTR-WM03-D-IN)



Junction Box  
Code: UTR-JB03-G-IN



Wall Mount  
Code: UTR-WM03-D-IN



# SPECIFICATION



Camera	<b>UIPC3615SE-ADF28KM-WL-I0</b>				
Sensor	1/2.7 5MP progressive scan, CMOS				
Lens	2.8mm@F1.0				
Iris	Fixed				
DORI Distance	Lens	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	2.8mm	63.0	25.2	12.6	6.3
Angle of View (H)	102.0°				
Angle of View (V)	53.4				
Angle of View (O)	121.0				
Adjustment angle	Pan: 3° ~ 360°		Tilt: 0° ~ 80°	Rotate: 3° ~ 360°	
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.001 Lux (F1.0, AGC ON)				
S/N	>56dB				
Defog	Digital Defog				
WDR	120dB				
LEDs Number	2 LED				
White Light Distance	Up to 30m (98ft)				
<b>Video</b>					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main profile, High profile				
Frame Rate	Main Stream: 5MP (2880*1620), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 25fps; 2MP (1920*1080), Max 30fps;				
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF (352*288), Max 30fps;				
	Third Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF (704*288), Max 30fps; CIF (352*288), Max 30fps;				
Video Bit Rate	128 Kbps~16 Mbps				
9:16 Corridor Mode	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
<b>Image</b>					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Smart Illumination	White Light				
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise				
Dewarping	N/A				
HLC	Support				
BLC	Support				
<b>Audio</b>					
Audio Compression	G.711				
Suppression	Supported				
Sampling Rate	8KHZ				

Camera	UIPC3615SE-ADF28KM-WL-I0
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR, NAS(NFS) Network
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Built-in Mic	Supported
Network	1 RJ45 10M/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1
	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 7.5W
Dimensions (Ø x H)	Φ110.5 x 94.1mm (Ø4.4" x 3.7")
Net Weight	0.44kg (0.97lb)
Material	metal
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
surge protection	2KV
Ingress Protection	IP67

**UNV AI SMART ANALYTICS**

**N O W   A V A I L A B L E**

Ensure accuracy and eliminate false alarms with AI SMART analytics which allow you to distinguish between types of vehicles & pedestrians!